

POWER KING®

TOWMAX

LOAD/INFLATION INFORMATION FOR ST METRIC TRAILER TIRES

FOR ST TRAILER TIRES USED IN NORMAL HIGHWAY SERVICE

Tire Size	Max Speed Rating (MPH)	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES (PSI)											
		25	30	35	40	45	50	55	60	65	70	75	80
ST205/75R14	65	1170	1300	1430 (B)	1530	1640	1760 (C)						
ST215/75R14	65	1270	1410	1520 (B)	1660	1790	1870 (C)						
ST205/75R15	65	1220	1360	1480 (B)	1610	1720	1820 (C)	1940	2040	2150 (D)			
ST225/75R15	65	1430	1600	1760 (B)	1880	2020	2150 (C)	2270	2380	2540 (D)	2620	2720	2830 (E)
ST175/80R13	65	905	1000	1100 (B)	1190	1270	1360 (C)						
ST185/80R13	65	990	1100	1200 (B)	1300	1400	1480 (C)						
ST235/80R16	65	1720	1920	2090 (B)	2270	2430	2600 (C)	2730	2870	3000 (D)	3140	3260	3520 (E)
ST235/85R16	65	1830	2040	2200 (B)	2400	2580	2760 (C)	2910	3060	3200 (D)	3360	3480	3640 (E)

Note: Letters in parentheses denote Load Range for which bold-faced loads and inflations are maximum