

2015 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
STD CAB - 6'4" Box 4x2 - HFE											
3.6L V6	A8 845RE	3.21	6010	1450	4556.68	2483.11	2073.57	3,700	3,900	9,850	4,980
STD CAB - 6'4" Box 4x2											
3.6L V6	A8 845RE	3.21	6025	1520	4509.89	2494.53	2015.36	3,700	3,900	9,850	4,960
3.6L V6	A8 845RE	3.55	6025	1520	4509.89	2494.53	2015.36	3,700	3,900	12,200	7,310
5.7L V8 HEMI	A6 65RFE	3.21	6350	1610	4738.68	2697.44	2041.24	3,700	3,900	12,350	7,160
5.7L V8 HEMI	A6 65RFE	3.92	6350	1610	4738.68	2697.44	2041.24	3,700	3,900	14,325	9,140
5.7L V8 HEMI	A8 8HP70	3.21	6350	1600	4747.98	2697.30	2050.68	3,700	3,900	13,800	8,630
5.7L V8 HEMI	A8 8HP70	3.92	6350	1600	4747.98	2697.30	2050.68	3,700	3,900	14,350	9,180
STD CAB - 6'4" Box 4x4											
3.6L V6	A8 845RE	3.21	6300	1580	4724.83	2666.72	2058.11	3,900	3,900	9,850	4,770
3.6L V6	A8 845RE	3.55	6300	1580	4724.83	2666.72	2058.11	3,900	3,900	12,200	7,060
5.7L V8 HEMI	A6 65RFE	3.55	6350	1430	4916.59	2850.86	2065.73	3,900	3,900	14,400	9,050
5.7L V8 HEMI	A6 65RFE	3.92	6350	1430	4916.59	2850.86	2065.73	3,900	3,900	14,325	8,970
5.7L V8 HEMI	A8 8HP70	3.21	6350	1430	4921.98	2909.27	2012.71	3,900	3,900	13,800	8,420
5.7L V8 HEMI	A8 8HP70	3.92	6350	1430	4921.98	2909.27	2012.71	3,900	3,900	14,350	8,970

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
8. The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN) and/or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2015 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant												
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating	
					Total	Front	Rear	Front	Rear			
STD CAB - 8' Box 4x2												
3.6L V6	A8 845RE	3.21	6600	1900	4704.48	2653.48	2051.00	3,700	3,900	9,850	4,790	
3.6L V6	A8 845RE	3.55	6600	1900	4704.48	2653.48	2051.00	3,700	3,900	12,400	7,280	
5.7L V8 HEMI	A6 65RFE	3.21	6600	1720	4878.02	2837.29	2040.73	3,700	3,900	12,350	7,050	
5.7L V8 HEMI	A6 65RFE	3.55	6600	1720	4878.02	2837.29	2040.73	3,700	3,900	14,400	9,100	
5.7L V8 HEMI	A6 65RFE	3.92	6600	1720	4878.02	2837.29	2040.73	3,700	3,900	15,950	10,650	
5.7L V8 HEMI	A8 8HP70	3.21	6600	1710	4888.36	2880.94	2007.42	3,700	3,900	13,800	8,490	
5.7L V8 HEMI	A8 8HP70	3.92	6600	1710	4888.36	2880.94	2007.42	3,700	3,900	15,950	10,640	
3.0L V6 ECODIESEL	A8 8HP70	3.55	6600	1500	5095.28	2985.77	2109.51	3,700	3,900	13,750	8,240	
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1500	5095.28	2985.77	2109.51	3,700	3,900	13,750	8,240	
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1500	5095.28	2985.77	2109.51	3,700	3,900	14,750	9,200	
STD CAB - 8' Box 4x4												
3.6L V6	A8 845RE	3.21	6600	1710	4887.32	2829.59	2057.73	3,900	3,900	9,850	4,610	
3.6L V6	A8 845RE	3.55	6600	1710	4887.32	2829.59	2057.73	3,900	3,900	12,400	7,110	
5.7L V8 HEMI	A6 65RFE	3.55	6600	1500	5102.06	3012.70	2089.36	3,900	3,900	14,400	8,880	
5.7L V8 HEMI	A6 65RFE	3.92	6600	1500	5102.06	3012.70	2089.36	3,900	3,900	15,950	10,430	
5.7L V8 HEMI	A8 8HP70	3.21	6600	1510	5092.36	3018.37	2073.99	3,900	3,900	13,800	8,300	
5.7L V8 HEMI	A8 8HP70	3.92	6600	1510	5092.36	3018.37	2073.99	3,900	3,900	15,950	10,450	
3.0L V6 ECODIESEL	A8 8HP70	3.55	6600	1290	5307.09	3151.95	2155.14	3,900	3,900	13,750	8,030	
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1290	5307.09	3151.95	2155.14	3,900	3,900	13,750	8,030	
3.0L V6 ECODIESEL	A8 8HP70	3.92	6600	1290	5307.09	3151.95	2155.14	3,900	3,900	14,750	9,030	

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
8. The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN) and/or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2015 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
QUAD CAB - 6'4" Box 4x2											
3.6L V6	A8 845RE	3.21	6800	1900	4904.84	2723.27	2181.57	3,700	3,900	9,850	4,620
3.6L V6	A8 845RE	3.55	6800	1900	4904.84	2723.27	2181.57	3,700	3,900	12,900	7,600
5.7L V8 HEMI	A6 65RFE	3.21	6900	1820	5082.36	2920.68	2161.68	3,700	3,900	12,350	6,790
5.7L V8 HEMI	A6 65RFE	3.55	6900	1820	5082.36	2920.68	2161.68	3,700	3,900	14,400	8,840
5.7L V8 HEMI	A6 65RFE	3.92	6900	1820	5082.36	2920.68	2161.68	3,700	3,900	15,950	10,390
5.7L V8 HEMI	A8 8HP70	3.21	6900	1780	5120.08	2947.25	2172.83	3,700	3,900	13,800	8,210
5.7L V8 HEMI	A8 8HP70	3.92	6900	1780	5120.08	2947.25	2172.83	3,700	3,900	15,950	10,360
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1610	5337.41	3024.53	2312.88	3,700	3,900	13,750	7,950
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1610	5337.41	3024.53	2312.88	3,700	3,900	13,750	7,950
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1610	5337.41	3024.53	2312.88	3,700	3,900	14,750	8,950
QUAD CAB - 6'4" Box 4x4											
3.6L V6	A8 845RE	3.21	6800	1720	5080.58	2895.29	2185.29	3,900	3,900	9,850	4,450
3.6L V6	A8 845RE	3.55	6800	1720	5080.58	2895.29	2185.29	3,900	3,900	12,900	7,440
5.7L V8 HEMI	A6 65RFE	3.55	6900	1600	5297.06	3098.74	2198.32	3,900	3,900	14,400	8,670
5.7L V8 HEMI	A6 65RFE	3.92	6900	1600	5297.06	3098.74	2198.32	3,900	3,900	15,950	10,220
5.7L V8 HEMI	A8 8HP70	3.21	6900	1600	5304.81	3106.54	2198.27	3,900	3,900	13,800	8,060
5.7L V8 HEMI	A8 8HP70	3.92	6900	1600	5304.81	3106.54	2198.27	3,900	3,900	15,950	10,210
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1400	5552.05	3245.02	2307.03	3,900	3,900	13,750	7,690
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1400	5552.05	3245.02	2307.03	3,900	3,900	13,750	7,690
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1400	5552.05	3245.02	2307.03	3,900	3,900	14,750	8,690

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
8. The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN) and/or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2015 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
CREW CAB - 5'7" Box 4x2											
3.6L V6	A8 845RE	3.21	6800	1850	4949.08	2723.01	2226.07	3,700	3,900	9,850	4,490
3.6L V6	A8 845RE	3.55	6800	1850	4949.08	2723.01	2226.07	3,700	3,900	12,900	7,480
5.7L V8 HEMI	A6 65RFE	3.21	6900	1770	5133.47	2922.55	2210.92	3,700	3,900	12,350	6,770
5.7L V8 HEMI	A6 65RFE	3.55	6900	1770	5133.47	2922.55	2210.92	3,700	3,900	14,400	8,820
5.7L V8 HEMI	A6 65RFE	3.92	6900	1770	5133.47	2922.55	2210.92	3,700	3,900	15,950	10,370
5.7L V8 HEMI	A8 8HP70	3.21	6900	1710	5193.96	2946.97	2246.99	3,700	3,900	13,800	8,170
5.7L V8 HEMI	A8 8HP70	3.92	6900	1710	5193.96	2946.97	2246.99	3,700	3,900	15,950	10,320
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1540	5407.88	3089.70	2318.18	3,700	3,900	13,750	7,840
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1540	5407.88	3089.70	2318.18	3,700	3,900	13,750	7,840
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1540	5407.88	3089.70	2318.18	3,700	3,900	14,750	8,840
CREW CAB - 5'7" Box 4x4											
3.6L V6	A8 845RE	3.21	6800	1650	5150.72	2892.01	2258.71	3,900	3,900	9,850	4,190
3.6L V6	A8 845RE	3.55	6800	1650	5150.72	2892.01	2258.71	3,900	3,900	12,900	7,180
5.7L V8 HEMI	A6 65RFE	3.55	6900	1550	5347.71	3098.76	2248.95	3,900	3,900	14,400	8,610
5.7L V8 HEMI	A6 65RFE	3.92	6900	1550	5347.71	3098.76	2248.95	3,900	3,900	15,950	10,160
5.7L V8 HEMI	A8 8HP70	3.21	6900	1530	5365.60	3105.31	2260.29	3,900	3,900	13,800	8,000
5.7L V8 HEMI	A8 8HP70	3.92	6900	1530	5365.60	3105.31	2260.29	3,900	3,900	15,950	10,150
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1340	5611.10	3245.51	2365.59	3,900	3,900	13,750	7,660
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1340	5611.10	3245.51	2365.59	3,900	3,900	13,750	7,660
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1340	5611.10	3245.51	2365.59	3,900	3,900	14,750	8,560

- 1 Payload and Max Trailer Weights are ESTIMATED values.
- 2 All weights are shown in pounds unless otherwise stated.
- 3 Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- 4 Payload = GVWR – Base Weight.
- 5 Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 Passenger Weight = 300 lb.
 Options Weight is option content above 33 percent of sales volume.
 Trailer equipment weight =
 Class IV receiver hitch is 11.1 lb (if not already included in options weight).
 Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- 6 Payload and Trailer Weight Rating are mutually exclusive.
- 7 GAWRs, GVWRs and GCWRs should never be exceeded.
8. The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100lb.
- 9 Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- 10 Quad Cab and Crew Cab models with Off Road Tire (s/c TXN) and/or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- 11 All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- 12 Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.

2015 RAM 1500 Trailer Towing Chart - SAE J2807 Compliant											
Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max. Trailer Weight Rating
					Total	Front	Rear	Front	Rear		
CREW CAB - 6'4" Box 4x2											
5.7L V8 HEMI	A6 65RFE	3.21	6900	1710	5192.97	2939.89	2253.08	3,700	3,900	12,350	6,740
5.7L V8 HEMI	A6 65RFE	3.55	6900	1710	5192.97	2939.89	2253.08	3,700	3,900	14,400	8,790
5.7L V8 HEMI	A6 65RFE	3.92	6900	1710	5192.97	2939.89	2253.08	3,700	3,900	15,950	10,340
5.7L V8 HEMI	A8 8HP70	3.21	6900	1660	5235.44	2966.66	2268.78	3,700	3,900	13,800	8,070
5.7L V8 HEMI	A8 8HP70	3.92	6900	1660	5235.44	2966.66	2268.78	3,700	3,900	15,950	10,220
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1480	5471.28	3150.79	2320.49	3,700	3,900	13,750	7,880
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1480	5471.28	3150.79	2320.49	3,700	3,900	13,750	7,880
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1480	5471.28	3150.79	2320.49	3,700	3,900	14,750	8,880
CREW CAB - 6'4" Box 4x4											
5.7L V8 HEMI	A6 65RFE	3.55	6900	1520	5384.92	3095.55	2289.37	3,900	3,900	14,400	8,550
5.7L V8 HEMI	A6 65RFE	3.92	6900	1520	5384.92	3095.55	2289.37	3,900	3,900	15,950	10,100
5.7L V8 HEMI	A8 8HP70	3.21	6900	1480	5420.01	3123.81	2296.20	3,900	3,900	13,800	7,800
5.7L V8 HEMI	A8 8HP70	3.92	6900	1480	5420.01	3123.81	2296.20	3,900	3,900	15,850	9,850
3.0L V6 ECODIESEL	A8 8HP70	3.55	6950	1270	5675.63	3359.62	2316.01	3,900	3,900	13,750	7,590
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1270	5675.63	3359.62	2316.01	3,900	3,900	13,750	7,590
3.0L V6 ECODIESEL	A8 8HP70	3.92	6950	1270	5675.63	3359.62	2316.01	3,900	3,900	14,550	8,390

- Payload and Max Trailer Weights are ESTIMATED values.
- All weights are shown in pounds unless otherwise stated.
- Payload and Max Trailer Weight values are rounded to the nearest 10 lb.
- Payload = GVWR – Base Weight.
- Trailer Weight Rating and Tow Vehicle Trailing Weight are calculated as specified in SAE J2807.
Passenger Weight = 300 lb.
Options Weight is option content above 33 percent of sales volume.
Trailer equipment weight =
Class IV receiver hitch is 11.1 lb (if not already included in options weight).
Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.
- Payload and Trailer Weight Rating are mutually exclusive.
- GAWRs, GVWRs and GCWRs should never be exceeded.
- The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1100lb.
- Weight Distributing Hitch is recommended for trailers over 5,000 lb.
- Quad Cab and Crew Cab models with Off Road Tire (s/c TXN) and/or Steel Wheel (s/c WFP) have 6800 lb GVWR.
- All models with 22 inch Tires (s/c TY4) have 6200 lb GVWR.
- Big Horn and Lone Star packages equipped with the 3.0L V6 EcoDiesel Engine and a 3.92 axle ratio have 13,750 lb. GCWR.