

Step 1 5th Wheel/Gooseneck Worksheet Instructions For CAT Scale (Do not use for conventional towing hitches.)	Answer Space Section A
Tow Vehicle (TV) Information: Enter the front Gross Axle Weight Rating (GAWR) found on the certification label usually located near the driver's side door. The front GAWR is the maximum allowable weight on the front axle assembly measured at the tires.	1 TV FRONT GAWR
Enter the rear Gross Axle Weight Rating (GAWR) found on the certification label usually located near the driver's side door. The rear GAWR is the maximum allowable weight on the rear axle assembly measured at the tires.	2 TV REAR GAWR
Enter the Gross Vehicle Weight Rating (GVWR) found on the certification label usually located near the driver's side door. The GVWR is the maximum allowable weight of the fully loaded TV, including liquids, passengers, cargo and kingpin or tongue weight of any towed trailer.	3 TV GVWR
Enter the Gross Combined Weight Rating (GCWR). The GCWR may be found in the "Owner's Manual" or in the TV brochure for the model year you own, usually provided by the dealership. This information may be found in Fifth Wheel St.'s "Towing Guides". The GCWR is the maximum allowable weight of the TV and the trailer combined. GCWR assumes that the TV and trailer have functioning brakes, with exceptions, in some cases, for very light trailers (normally less than 1,500 pounds).	4 TV GCWR
Hitch Information: Enter the Gross Trailer Weight Rating (GTWR) of the hitch: The GTWR may be written on a label or stamped somewhere on the 5th wheel hitch. The hitch GTWR can also be provided by the manufacturer.	5 HITCH GTWR
Trailer Information: Enter the trailer's Gross Vehicle Weight Rating (GVWR). The trailer GVWR may be found near the pin box, inside a kitchen door cabinet of the RV, on the front quarter of the off-door side (driver's side) of the RV or by provided the manufacturer. Trailer GVWR is the maximum allowable combined weight of the trailer and all the contents, such as liquids, passengers, cargo, etc.	6 TRAILER GVWR
Weighing the TV and Trailer at CAT Scale: Step two (2) and step three (3) may be completed in any order of convenience. To achieve the most accurate report, perform steps two (2) and three (3) during the same visit at CAT Scale. Always park and disconnect your trailer safely in the designated spaces. Never disconnect your trailer on the scale. Drive with the fully loaded TV and attached trailer to the nearest CAT Scale location. The cost is \$14.50 plus \$2.00 reweigh fee within 24 hours at the same location. CAT Scale has made the process of weighing your TV and trailer effortless. If you haven't done so, read the CAT Scale "RV Weighing Guide". It is important that your TV and trailer are fully loaded, including liquids, passengers and cargo. When you arrive at the scale, inform the scale operator in the facility you are a noncommercial RV owner. CAT Scale also has a free Smart Phone scale locator app.	
Step 2: Weigh the TV with the trailer attached. Three weight measurements are required for step 2: TV front tires (steering axle), TV rear tires (drive axle) and all trailer tires (axles). Drive onto the scale so that your steer axle is positioned on platform 1, your drive axle on platform 2 and your trailer axles on platform 3. Upon receiving your printout from the scale operator, enter the weights on the right.	<div data-bbox="990 1438 1274 1554" data-label="Image"> </div> Section B A TV Steer Axle B TV Drive Axle C Trailer Axle(s)
Step 3: Weigh the TV without the trailer attached. Two weight measurements are required for step 3: TV front tires (steering axle) and the TV rear tires (drive axle). Drive onto the scale so that your steer axle is positioned on platform 1 and your drive axle on platform 2. Upon receiving your printout from the scale operator, enter the weights on the right.	<div data-bbox="990 1732 1274 1837" data-label="Image"> </div> D TV Steer Axle E TV Drive Axle
Copyright © 2011-2014 Fifth Wheel St. All rights reserved. Permission granted to print for personal use only.	