

MICHELIN INFLATION CHARTS FOR TRUCK TIRES

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

WHEEL DIAMETER - 15"

10.00R15 LRJ

XTA®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	S	6940	LBS at	120 PSI
	DUAL	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580	D	6395	LBS at	120 PSI
KG	SINGLE	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	S	3150	KG at	830 kPa
	DUAL	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600	D	2900	KG at	830 kPa

WHEEL DIAMETER - 16"

LT215/85R16 LRE

XPS TRACTION®, XPS RIB®

PSI		35	40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		240	280	310	340	380	410	450	480	520	550				
LBS	SINGLE	2990	3280	3570	3880	4110	4360	4670	4860	5100	5360	S	2680	LBS at	80 PSI
	DUAL	5440	5960	6500	7060	7446	7940	8600	8840	9280	9880	D	2470	LBS at	80 PSI
KG	SINGLE	1356	1488	1619	1760	1864	1978	2118	2204	2313	2430	S	1215	KG at	550 kPa
	DUAL	2468	2703	2948	3202	3378	3602	3901	4010	4209	4480	D	1120	KG at	550 kPa

LT225/75R16 LRE

XPS RIB®

PSI		40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		280	310	350	380	410	450	480	520	550					
LBS	SINGLE	3300	3580	3880	4120	4380	4670	4880	5120	5360		S	2680	LBS at	80 PSI
	DUAL	6000	6520	7060	7500	7980	8600	8880	9320	9880		D	2470	LBS at	80 PSI
KG	SINGLE	1497	1624	1760	1869	1987	2118	2214	2322	2431		S	1215	KG at	550 kPa
	DUAL	2722	2957	3202	3402	3620	3901	4028	4228	4482		D	1120	KG at	550 kPa

LT235/85R16 LRE

XPS TRACTION®, XPS RIB®

PSI		35	40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		250	280	310	350	380	410	450	480	520	550				
LBS	SINGLE	3480	3725	3970	4410	4630	4850	5246	5510	5820	6084	S	3042	LBS at	80 PSI
	DUAL	6340	6780	7220	8024	8422	8820	9524	10028	10592	11112	D	2778	LBS at	80 PSI
KG	SINGLE	1580	1690	1800	2000	2100	2200	2380	2500	2640	2760	S	1380	KG at	550 kPa
	DUAL	2880	3080	3280	3640	3820	4000	4320	4540	4800	5040	D	1260	KG at	550 kPa

LT245/75R16 LRE

XPS RIB®

PSI		35	40	45	50	55	60	65	70	75	80	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		250	280	310	350	380	410	450	480	520	550				
LBS	SINGLE	3400	3730	4060	4410	4670	4960	5250	5530	5800	6084	S	3042	LBS at	80 PSI
	DUAL	6180	6780	7380	8024	8500	9020	9525	10060	10560	11112	D	2778	LBS at	80 PSI
KG	SINGLE	1580	1690	1840	2000	2120	2250	2380	2510	2630	2760	S	1380	KG at	550 kPa
	DUAL	2880	3075	3350	3640	3855	4090	4320	4560	4790	5040	D	1260	KG at	550 kPa

WHEEL DIAMETER - 17"

7.50R17 LRD

XCA

PSI		45	50	55	60	65	70	75	MAXIMUM LOAD AND PRESSURE ON SIDEWALL						
kPa		310	340	380	410	450	480	520							
LBS	SINGLE	3720	4050	4370	4680	4990	5300	5600				S	2800	LBS at	75 PSI
	DUAL	6920	7520	8120	8700	9280	9840	10400				D	2600	LBS at	75 PSI
KG	SINGLE	1680	1800	1980	2100	2260	2380	2540				S	1270	KG at	520 kPa
	DUAL	3120	3360	3680	3920	4200	4440	4720				D	1180	KG at	520 kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

WHEEL DIAMETER - 17.5"

10R17.5 LRG

XZA[®]

PSI		85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa		590	620	660	690	720	760	790						
LBS	SINGLE	7720	8010	8300	8600	8940	9280	9610	S	4805	LBS at	115	PSI	
	DUAL	14560	15140	15720	16320	16940	17560	18160	D	4540	LBS at	115	PSI	
KG	SINGLE	3500	3640	3780	3900	4060	4220	4360	S	2180	KG at	790	kPa	
	DUAL	6600	6880	7160	7400	7680	7960	8240	D	2060	KG at	790	kPa	

215/75R17.5 LRG

XZE[®] 2

PSI		55	60	65	70	75	80	85	90	95	100	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		380	410	450	480	520	550	590	620	660	690					
LBS	SINGLE	4650	4980	5310	5640	5960	6270	6590	6890	7200	7500	S	3750	LBS at	100	PSI
	DUAL	8740	9380	9980	10600	11200	11800	12380	12960	13540	14100	D	3525	LBS at	100	PSI
KG	SINGLE	2110	2240	2420	2540	2720	2840	3000	3120	3280	3400	S	1700	KG at	690	kPa
	DUAL	3960	4240	4560	4800	5120	5320	5640	5880	6160	6400	D	1600	KG at	690	kPa

215/75R17.5 LRJ

XTA[®]

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	6750	7080	7390	7720	8020	8360	8660	8990	9300	9610	S	4805	LBS at	120	PSI
	DUAL	12790	13400	14000	14590	15190	15780	16380	16980	17570	18160	D	4540	LBS at	120	PSI
KG	SINGLE	3062	3211	3352	3502	3638	3792	3928	4078	4218	4360	S	2180	KG at	830	kPa
	DUAL	5802	6078	6350	6618	6890	7158	7430	7702	7970	8240	D	2060	KG at	830	kPa

235/75R17.5 LRJ

XTE2[®]

PSI		80	85	90	95	100	105	110	115	120	125	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660	690	720	760	790	830	860					
LBS	SINGLE	8400	8820	9230	9640	10050	10450	10840	11240	11620	12010	S	6005	LBS at	125	PSI
	DUAL	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700	D	5675	LBS at	125	PSI
KG	SINGLE	3820	4040	4200	4400	4560	4720	4940	5100	5300	5450	S	2725	KG at	860	kPa
	DUAL	7200	7600	7920	8320	8640	8920	9320	9640	10000	10300	D	2575	KG at	860	kPa

245/70R17.5 LRJ

XTA[®] 2 ENERGY

PSI		80	85	90	95	100	105	110	115	120	125	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660	690	720	760	790	830	860					
LBS	SINGLE	8400	8820	9230	9640	10050	10450	10840	11240	11620	12010	S	6005	LBS at	125	PSI
	DUAL	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700	D	5675	LBS at	125	PSI
KG	SINGLE	3820	4040	4200	4400	4560	4720	4940	5100	5300	5450	S	2725	KG at	860	kPa
	DUAL	7200	7600	7920	8320	8640	8920	9320	9640	10000	10300	D	2575	KG at	860	kPa

WHEEL DIAMETER - 19.5"

225/70R19.5 LRF

XZE[®], XRV[®], XDS[®] 2

PSI		65	70	75	80	85	90	95	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		450	480	520	550	590	620	660					
LBS	SINGLE	5510	5790	6080	6390	6630	6900	7280	S	3640	LBS at	95	PSI
	DUAL	10400	10880	11440	12000	12460	12980	13660	D	3415	LBS at	95	PSI
KG	SINGLE	2500	2620	2760	2900	3000	3140	3300	S	1650	KG at	660	kPa
	DUAL	4720	4920	5200	5440	5640	5880	6200	D	1550	KG at	660	kPa

225/70R19.5 LRG

XZE[®], XDS[®] 2

PSI		65	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		450	480	520	550	590	620	660	690	720	760					
LBS	SINGLE	5510	5790	6080	6390	6630	6900	7280	7430	7690	7940	S	3970	LBS at	110	PSI
	DUAL	10400	10880	11440	12000	12460	12980	13660	13960	14460	15000	D	3750	LBS at	110	PSI
KG	SINGLE	2500	2620	2760	2900	3000	3140	3300	3380	3480	3600	S	1800	KG at	760	kPa
	DUAL	4720	4920	5200	5440	5640	5880	6200	6320	6560	6800	D	1700	KG at	760	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

245/70R19.5 LRF **XRV®**

PSI		80	85	90	95						MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		550	590	620	660										
LBS	SINGLE	7280	7480	7780	8160						S	4080	LBS at	95	PSI
	DUAL	13660	14060	14620	15440						D	3860	LBS at	95	PSI
KG	SINGLE	3300	3400	3540	3700						S	1850	KG at	660	kPa
	DUAL	6200	6360	6640	7000						D	1750	KG at	660	kPa

245/70R19.5 LRH **XZE®, XDS®2**

PSI		75	80	85	90	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa		520	550	590	620	660	690	720	760	830						
LBS	SINGLE	6780	7140	7500	7850	8200	8540	8880	9220	9550	9880	S	4940	LBS at	120	PSI
	DUAL	12840	13520	14200	14860	15520	16160	16800	17440	18080	18700	D	4675	LBS at	120	PSI
KG	SINGLE	3080	3220	3400	3540	3720	3860	4000	4180	4300	4480	S	2240	KG at	830	kPa
	DUAL	5840	6120	6440	6720	7040	7320	7560	7920	8160	8480	D	2120	KG at	830	kPa

265/70R19.5 LRG **XZE®2+, XDE®2+**

PSI		65	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		450	480	520	550	590	620	660	690	720	760					
LBS	SINGLE	7230	7680	8110	8540	8970	9390	9800	10210	10620	11020	S	5510	LBS at	110	PSI
	DUAL	13660	14500	15320	16140	16940	17740	18520	19300	20060	20820	D	5205	LBS at	110	PSI
KG	SINGLE	3280	3460	3700	3860	4080	4240	4460	4620	4780	5000	S	2500	KG at	760	kPa
	DUAL	6200	6520	6960	7280	7720	8040	8440	8720	9040	9440	D	2360	KG at	760	kPa

265/70R19.5 LRH **X Line™ Energy T 19.5**

PSI		75	80	85	90	95	100	105	110	115	123	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	850					
LBS	SINGLE	8250	8680	9110	9540	9960	10380	10790	11200	11610	12010	S	6005	LBS at	123	PSI
	DUAL	15580	16420	17220	18040	18840	19620	20400	21180	21940	22700	D	5675	LBS at	123	PSI
KG	SINGLE	3740	3920	4140	4320	4540	4700	4860	5080	5240	5450	S	2725	KG at	850	kPa
	DUAL	7080	7400	7840	8160	8560	8880	9200	9600	9920	10300	D	2575	KG at	850	kPa

285/70R19.5 LRH **XZE®2+, XDE®2+**

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	8780	9250	9710	10160	10610	11050	11490	11930	12360	12790	S	6395	LBS at	120	PSI
	DUAL	16500	17360	18220	19080	19920	20760	21580	22400	23220	24020	D	6005	LBS at	120	PSI
KG	SINGLE	3980	4180	4420	4600	4820	5000	5180	5400	5580	5800	S	2900	KG at	830	kPa
	DUAL	7480	7840	8280	8640	9080	9400	9720	10160	10480	10900	D	2725	KG at	830	kPa

285/70R19.5 LRJ **XTE2®**

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	10520	11010	11500	11980	12460	12930	13400	13860	14320	14780	S	7390	LBS at	130	PSI
	DUAL	19760	20680	21600	22500	23400	24280	25160	26040	26920	27760	D	6940	LBS at	130	PSI
KG	SINGLE	4770	4990	5220	5430	5650	5860	6080	6290	6500	6700	S	3350	KG at	900	kPa
	DUAL	8960	9380	9800	10210	10610	11010	11410	11810	12210	12600	D	3150	KG at	900	kPa

305/70R19.5 LRJ **XZA®**

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	S	6940	LBS at	120	PSI
	DUAL	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580	D	6395	LBS at	120	PSI
KG	SINGLE	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	S	3150	KG at	830	kPa
	DUAL	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600	D	2900	KG at	830	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

Industry load and inflation standards are in a constant state of change, and Michelin continually

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

445/45R19.5 LRM XTA2+ ENERGY

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	14120	14780	15440	16080	16720	17360	17980	18600	19220	19840	S	9920	LBS at	130	PSI
	DUAL											D		LBS at		PSI
KG	SINGLE	6420	6680	7020	7280	7520	7860	8100	8440	8680	9000	S	4500	KG at	900	kPa
	DUAL											D		KG at		kPa

WHEEL DIAMETER - 20"

G20 (14.00R20) XZA[®]4

PSI		70	75	80	85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760	790					
LBS	SINGLE	15660	16500	17200	18180	18920	19660	20400	20940	21480	22000	S	11000	LBS at	115	PSI
	DUAL	28640	30120	31600	33080	34560	36040	37480	38600	39720	40800	D	10200	LBS at	115	PSI
KG	SINGLE	7100	7480	7860	8250	8580	8920	9250	9500	9760	10000	S	5000	KG at	790	kPa
	DUAL	13000	13680	14360	15000	15680	16360	17000	17520	18040	18500	D	4625	KG at	790	kPa

365/80R20 LRF null

PSI		45	50	55	60	65	70	75	80	85	90	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		310	340	380	410	450	480	520	550	590	620					
LBS	SINGLE	8990	9790	10560	11320	12070	12810	13540	14260	14960	15660	S	7830	LBS at	90	PSI
	DUAL											D		LBS at		PSI
KG	SINGLE	4080	4400	4800	5100	5500	5780	6160	6460	6820	7100	S	3550	KG at	620	kPa
	DUAL											D		KG at		kPa

365/85R20 LRJ XZL[™]

PSI		70	75	80	85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760	790					
LBS	SINGLE	14780	15620	16460	17280	18080	18880	19680	20400	21200	22000	S	11000	LBS at	115	PSI
	DUAL											D		LBS at		PSI
KG	SINGLE	6720	7160	7480	7920	8240	8660	8980	9280	9700	10000	S	5000	KG at	790	kPa
	DUAL											D		KG at		kPa

395/85R20 LRG XZL[™]

PSI		80	85	90	95	MAXIMUM LOAD AND PRESSURE ON SIDEWALL						
kPa		550	590	620	660							
LBS	SINGLE	16820	17560	18280	18740	S	9370	LBS at	95	PSI		
	DUAL					D		LBS at		PSI		
KG	SINGLE	7640	7960	8280	8500	S	4250	KG at	660	kPa		
	DUAL					D		KG at		kPa		

WHEEL DIAMETER - 20.5"

24R20.5 LRH XST[™]

PSI		40	45	50	55	60	65	70	75	80	85	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		280	310	340	380	410	450	480	520	550	590					
LBS	SINGLE	17180	18880	20600	22200	23800	25400	26800	28400	30000	31400	S	15700	LBS at	85	PSI
	DUAL											D		LBS at		PSI
KG	SINGLE	7820	8480	9140	9980	10620	11440	12040	12840	13420	14200	S	7100	KG at	590	kPa
	DUAL											D		KG at		kPa

WHEEL DIAMETER - 21"

24R21 LRH XZL[™]

PSI		40	45	50	55	60	65	70	75	80	85	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		280	310	340	380	410	450	480	520	550	590					
LBS	SINGLE	17180	18880	20600	22200	23800	25400	26800	28400	30000	31400	S	15700	LBS at	85	PSI
	DUAL											D		LBS at		PSI
KG	SINGLE	7820	8480	9140	9980	10620	11440	12040	12840	13420	14200	S	7100	KG at	590	kPa
	DUAL											D		KG at		kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

WHEEL DIAMETER - 22.5"

9R22.5 LRF

XZE[®]

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720					
LBS	SINGLE	6740	7120	7460	7780	8160	8470	8780	9080	S	4540	LBS at	105	PSI
	DUAL	13080	13640	14200	14760	15440	16020	16600	17200	D	4300	LBS at	105	PSI
KG	SINGLE	3060	3230	3380	3520	3700	3840	3980	4120	S	2060	KG at	720	kPa
	DUAL	5920	6200	6440	6680	7000	7280	7560	7800	D	1950	KG at	720	kPa

10R22.5 LRF

XZE[®]

PSI		70	75	80	85	90	95	100	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa		480	520	550	590	620	660	690						
LBS	SINGLE	8160	8560	8960	9350	9700	10050	10410		S	5205	LBS at	100	PSI
	DUAL	15440	16180	16920	17640	18340	19040	19760		D	4940	LBS at	100	PSI
KG	SINGLE	3700	3880	4060	4240	4400	4560	4720		S	2360	KG at	690	kPa
	DUAL	7000	7320	7640	8000	8320	8640	8960		D	2240	KG at	690	kPa

10R22.5 LRG

XZE[®], XDE[®] M/S

PSI		70	75	80	85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760	790					
LBS	SINGLE	8160	8560	8960	9350	9700	10050	10410	10720	11030	11350	S	5675	LBS at	115	PSI
	DUAL	15440	16180	16920	17640	18340	19040	19760	20300	20840	21420	D	5355	LBS at	115	PSI
KG	SINGLE	3700	3880	4060	4240	4400	4560	4720	4860	5000	5150	S	2575	KG at	790	kPa
	DUAL	7000	7320	7640	8000	8320	8640	8960	9200	9440	9720	D	2430	KG at	790	kPa

11R22.5 LRG

XZY[®] 3, XZE2[™], XZA3[®]+ EVERTREAD[™], XZA[®]-1+, XTE[®], XDN[®]2, XDE[®] M/S, XDA[®]5+, X[®]MULTI[™]ENERGY D, X[®]Line[™] Energy T, X[®]Line[™] Energy D

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa		480	520	550	590	620	660	690	720						
LBS	SINGLE	9060	9540	9980	10440	11020	11460	11900	12350		S	6175	LBS at	105	PSI
	DUAL	17520	18320	19040	19800	20820	21660	22500	23360		D	5840	LBS at	105	PSI
KG	SINGLE	4100	4320	4520	4740	5000	5200	5400	5600		S	2800	KG at	720	kPa
	DUAL	7960	8320	8640	9000	9440	9840	10240	10600		D	2650	KG at	720	kPa

11R22.5 LRH

XZY[®] 3, XZE2[™], XZA3[®]+ EVERTREAD[™], XDS[®]2, XDN[®]2, XDE[®] M/S*, X Works XDY[®]

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220	S	6610	LBS at	120	PSI
	DUAL	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020	D	6005	LBS at	120	PSI
KG	SINGLE	4320	4520	4740	5000	5200	5400	5600	5740	5880	6000	S	3000	KG at	830	kPa
	DUAL	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900	D	2725	KG at	830	kPa

11R22.5 LRH

XZU[®]3, XDE[®]2+

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	S	6940	LBS at	120	PSI
	DUAL	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580	D	6395	LBS at	120	PSI
KG	SINGLE	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	S	3150	KG at	830	kPa
	DUAL	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600	D	2900	KG at	830	kPa

12R22.5 LRH

XZY[®] 3, XZE[®]*, XDS[®], XDN[®]2

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	10400	10900	11380	12010	12410	12810	13220	13740	14260	14780	S	7390	LBS at	120	PSI
	DUAL	19960	20760	21560	22700	23140	23580	24020	25060	26100	27120	D	6780	LBS at	120	PSI
KG	SINGLE	4720	4940	5160	5450	5640	5820	6000	6240	6480	6700	S	3350	KG at	830	kPa
	DUAL	9040	9400	9760	10300	10520	10720	10900	11360	11840	12300	D	3075	KG at	830	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

12R22.5 LRJ **xzu[®]2**

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660	S	7830	LBS at 120	PSI
	DUAL	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760	D	6940	LBS at 120	PSI
KG	SINGLE	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100	S	3550	KG at 830	kPa
	DUAL	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600	D	3150	KG at 830	kPa

235/80R22.5 LRG **xze[®], xrv[®]**

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	480	520	550	590	620	660	690	720	760						
LBS	SINGLE	6940	7290	7720	7950	8280	8600	8910	9220	9350		S	4675	LBS at 110	PSI
	DUAL	12640	13260	14100	14460	15060	15880	16220	16780	17640		D	4410	LBS at 110	PSI
KG	SINGLE	3140	3300	3500	3600	3760	3900	4040	4180	4240		S	2120	KG at 760	kPa
	DUAL	5720	6000	6400	6560	6840	7200	7360	7600	8000		D	2000	KG at 760	kPa

255/80R22.5 LRG **xze[®], xrv[®]**

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	480	520	550	590	620	660	690	720	760						
LBS	SINGLE	7750	8140	8600	8880	9240	9610	9950	10300	10410		S	5205	LBS at 110	PSI
	DUAL	14100	14820	15440	16160	16820	17640	18100	18740	19220		D	4805	LBS at 110	PSI
KG	SINGLE	3520	3700	3900	4020	4200	4360	4520	4680	4720		S	2360	KG at 760	kPa
	DUAL	6400	6720	7000	7320	7640	8000	8200	8520	8720		D	2180	KG at 760	kPa

255/70R22.5 LRH **xze[®]*, xd2[®]**

PSI	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	550	590	620	660	690	720	760	790	830						
LBS	SINGLE	8380	8740	9100	9350	9790	10130	10410	10800	11020		S	5510	LBS at 120	PSI
	DUAL	15880	16440	17100	17640	17820	18440	18700	19660	20280		D	5070	LBS at 120	PSI
KG	SINGLE	3800	3960	4120	4240	4440	4600	4720	4900	5000		S	2500	KG at 830	kPa
	DUAL	7200	7440	7760	8000	8080	8360	8480	8920	9200		D	2300	KG at 830	kPa

275/80R22.5 LRG **xze2[™], xza3[®]+ EVERTREAD™, xza[®]-1+, xte[®], xdn[®]2, xde[®] M/S, xda[®]5+, xda[®] ENERGY, x[®] MULTI[™] ENERGY D, x[®] Line[™] Energy T, x[®] Line[™] Energy D**

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	480	520	550	590	620	660	690	720	760						
LBS	SINGLE	9000	9450	9880	10310	10740	11020	11560	11960	12350		S	6175	LBS at 110	PSI
	DUAL	16380	17200	18160	18760	19540	20280	21040	21760	22700		D	5675	LBS at 110	PSI
KG	SINGLE	4080	4280	4480	4680	4880	5000	5240	5420	5600		S	2800	KG at 760	kPa
	DUAL	7440	7800	8240	8520	8880	9200	9560	9880	10300		D	2575	KG at 760	kPa

275/80R22.5 LRH **xze[®], xza3[®]+ EVERTREAD™, xde[®]2+**

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	9830	10350	10870	11380	11880	12380	12870	13360	13840	14320	S	7160	LBS at 120	PSI
	DUAL	18160	19120	20060	21000	21940	22860	23760	24660	25560	26440	D	6610	LBS at 120	PSI
KG	SINGLE	4480	4680	4940	5140	5420	5600	5800	6060	6240	6500	S	3250	KG at 830	kPa
	DUAL	8240	8640	9120	9520	10000	10360	10720	11200	11520	12000	D	3000	KG at 830	kPa

275/70R22.5 LRJ **xty[®]2**

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	S	6940	LBS at 120	PSI
	DUAL	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580	D	6395	LBS at 120	PSI
KG	SINGLE	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	S	3150	KG at 830	kPa
	DUAL	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600	D	2900	KG at 830	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

275/70R22.5 LRJ XZU[®]2, XZE[®]2+, XZA2[®] Energy™

PSI	85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	9880	10340	10800	11250	11700	12140	12580	13020	13460	13880	S	6940	LBS at 130	PSI
	DUAL	19420	20320	21220	22100	22980	23860	24720	25580			D	6395	LBS at 120	PSI
KG	SINGLE	4480	4690	4900	5100	5310	5510	5710	5910	6110	6300	S	3150	KG at 900	kPa
	DUAL	8810	9220	9630	10020	10420	10820	11210	11600			D	2900	KG at 830	kPa

295/80R22.5 LRH XZA2[®] Energy™

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660	S	7830	LBS at 120	PSI
	DUAL	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760	D	6940	LBS at 120	PSI
KG	SINGLE	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100	S	3550	KG at 830	kPa
	DUAL	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600	D	3150	KG at 830	kPa

295/80R22.5 LRH XZE[®]2+

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	725	760	790	830					
LBS	SINGLE	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660	S	7830	LBS at 120	PSI
	DUAL	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760	D	6940	LBS at 120	PSI
KG	SINGLE	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100	S	3550	KG at 830	kPa
	DUAL	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600	D	3150	KG at 830	kPa

295/80R22.5 LRH X Coach HL Z

PSI	80	85	90	95	100	105	110	115	120	123	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	550	590	620	660	690	725	760	790	830	850					
LBS	SINGLE	11720	12310	12880	13460	14020	14580	15120	15680	16220	16540	S	8270	LBS at 123	PSI
	DUAL	20300	21320	22300	23300	24260	25240	26200	27120	28080	28640	D	7160	LBS at 123	PSI
KG	SINGLE	5300	5600	5820	6120	6340	6560	6860	7080	7360	7500	S	3750	KG at 850	kPa
	DUAL	9160	9720	10120	10600	11000	11400	11880	12280	12760	13000	D	3250	KG at 850	kPa

295/60R22.5 LRJ XZA2[®] Energy™, X MultiWay XD

PSI	85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	10520	11010	11500	11980	12460	12930	13400	13860	14320	14780	S	7390	LBS at 130	PSI
	DUAL	19300	20200	21100	21980	22860	23720	24580	25440	26280	27120	D	6780	LBS at 130	PSI
KG	SINGLE	4770	4990	5220	5430	5650	5860	6080	6290	6460	6700	S	3350	KG at 900	kPa
	DUAL	8750	9160	9570	9970	10370	10760	11150	11540	11920	12300	D	3075	KG at 900	kPa

295/80R22.5 LRJ X[®] Coach XZ

PSI	80	85	90	95	100	105	110	115	120	123	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	550	590	620	660	690	720	760	790	830	850					
LBS	SINGLE	10960	11520	12040	12580	13100	13600	14200	14640	15160	15660	S	7830	LBS at 123	PSI
	DUAL	19440	20400	21360	22280	23200	24160	25080	25960	26880	27760	D	6940	LBS at 123	PSI
KG	SINGLE	4960	5260	5460	5740	5960	6160	6440	6640	6900	7100	S	3550	KG at 850	kPa
	DUAL	8800	9320	9680	10200	10560	10920	11400	11760	12240	12600	D	3150	KG at 850	kPa

305/85R22.5 LRJ XZU[®]3

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	0	11680	12200	12700	13220	13660	14140	14780	15140	15660	S	7830	LBS at 120	PSI
	DUAL		21420	22200	23120	24020	24860	25740	27120	27680	28640	D	7160	LBS at 120	PSI
KG	SINGLE	0	5300	5540	5760	6000	6200	6420	6700	6820	7100	S	3550	KG at 830	kPa
	DUAL		9720	10080	10480	10900	11280	11680	12300	12480	13000	D	3250	KG at 830	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

305/70R22.5 LRL XZU[®]2, XRV[®]

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660	S	7830	LBS at 120	PSI
	DUAL	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760	D	6940	LBS at 120	PSI
KG	SINGLE	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100	S	3550	KG at 830	kPa
	DUAL	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600	D	3150	KG at 830	kPa

315/80R22.5 LRJ null

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	12110	12750	13380	14020	14640	15240	15860	16460	17040	17640	S	8820	LBS at 120	PSI
	DUAL	20300	21380	22440	23480	24520	25540	26560	27560	28560	29560	D	7390	LBS at 120	PSI
KG	SINGLE	5500	5760	6080	6340	6660	6900	7140	7460	7700	8000	S	4000	KG at 830	kPa
	DUAL	9200	9640	10200	10600	11160	11560	11960	12480	12880	13400	D	3350	KG at 830	kPa

315/80R22.5 LRL null

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	12110	12750	13380	14020	14640	15240	15860	16460	17040	17640	S	8820	LBS at 120	PSI
	DUAL	20300	21380	22440	23480	24520	25540	26560	27560	28560	29560	D	7390	LBS at 115	PSI
KG	SINGLE	5500	5760	6080	6340	6660	6900	7140	7460	7700	8000	S	4000	KG at 830	kPa
	DUAL	9200	9640	10200	10600	11160	11560	11960	12480	12880	13400	D	3350	KG at 790	kPa

315/80R22.5 LRL XZY[®]3, XZA2[®] Energy™, XZA[®]1, XDY[®]3, XDN[®]2 GRIP

PSI	85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	12940	13540	14140	14740	15320	15900	16480	17060	17620	18180	S	9090	LBS at 130	PSI
	DUAL	23540	24640	25740	26800	27880	28960	30000	31040	32040	33080	D	8270	LBS at 130	PSI
KG	SINGLE	5880	6120	6440	6680	6900	7200	7440	7740	7960	8250	S	4125	KG at 900	kPa
	DUAL	10680	11120	11720	12120	12560	13120	13520	14040	14480	15000	D	3750	KG at 900	kPa

315/80R22.5 LRL XZU[®]S2

PSI	85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	14240	14900	15560	16220	16860	17500	18140	18760	19380	20000	S	10000	LBS at 130	PSI
	DUAL	23540	24640	25740	26800	27880	28960	30000	31040	32040	33080	D	8270	LBS at 130	PSI
KG	SINGLE	6460	6740	7080	7340	7580	7920	8180	8500	8740	9070	S	4535	KG at 900	kPa
	DUAL	10680	11120	11720	12120	12560	13120	13520	14040	14480	15000	D	3750	KG at 900	kPa

365/70R22.5 LRL XZA[®]

PSI	80	85	90	95	100	105	110	115	120	125	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	550	590	620	660	690	720	760	790	830	860					
LBS	SINGLE	14700	15420	16140	16860	17560	18260	18960	19640	20400	21000	S	10500	LBS at 125	PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6640	7020	7320	7680	7960	8240	8600	8880	9240	9500	S	4750	KG at 860	kPa
	DUAL											D		KG at	kPa

385/65R22.5 LRJ XZY[®]3 Wide Base

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	13440	13880	14700	15300	16100	16460	17020	17640	18100	18740	S	9370	LBS at 120	PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6120	6300	6700	6940	7300	7480	7700	8000	8200	8500	S	4250	KG at 830	kPa
	DUAL											D		KG at	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

385/55R22.5 LRL X[®] Multi[™] T

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	14120	14780	15440	16080	16720	17360	17980	18600	19220	19840	S	9920	LBS at	130 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6420	6680	7020	7280	7520	7860	8100	8440	8680	9000	S	4500	KG at	900 kPa
	DUAL											D		KG at	kPa

385/65R22.5 LRL XFE[™] Wide Base

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	14120	14780	15440	16080	16720	17360	17980	18600	19220	19840	S	9920	LBS at	130 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6420	6680	7020	7280	7520	7860	8100	8440	8680	9000	S	4500	KG at	900 kPa
	DUAL											D		KG at	kPa

425/65R22.5 LRL XFE[™] Wide Base

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	825				
LBS	SINGLE	15660	16480	17300	18120	18920	19700	20400	21200	22000	22800	S	11400	LBS at	120 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	7080	7420	7840	8160	8580	8880	9200	9600	9900	10300	S	5150	KG at	825 kPa
	DUAL											D		KG at	kPa

425/65R22.5 LRL XZY[®] 3 Wide Base, XZU[®] S wb, XZL[™] Wide Base

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	15980	16540	17480	18200	18740	19580	20200	21000	21400	22800	S	11400	LBS at	120 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	7280	7500	7960	8260	8500	8880	9160	9500	9760	10300	S	5150	KG at	830 kPa
	DUAL											D		KG at	kPa

445/50R22.5 LRL X One[®] XTE[®], X One[®] XTA[®], X One[®] XDN[®] 2, X ONE[®] LINE[™] ENERGY D

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	13880	14620	15360	16060	16780	17480	18180	18740	19560	20400	S	10200	LBS at	120 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6300	6640	6960	7280	7620	7940	8240	8500	8860	9250	S	4625	KG at	830 kPa
	DUAL											D		KG at	kPa

445/65R22.5 LRL XZL[™] Wide Base

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	17320	18180	18960	19740	20400	21200	22000	22800	23400	24600	S	12300	LBS at	120 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	7900	8250	8640	8940	9250	9640	9920	10300	10580	11200	S	5600	KG at	830 kPa
	DUAL											D		KG at	kPa

445/65R22.5 LRL XZY[®] 3 Wide Base

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	18220	19080	19920	20800	21600	22400	23200	24000	24800	25600	S	12800	LBS at	130 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	8280	8600	9060	9380	9700	10140	10460	10880	11180	11600	S	5800	KG at	900 kPa
	DUAL											D		KG at	kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

Industry load and inflation standards are in a constant state of change, and Michelin continually

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

445/65R22.5 LRM XFE™ Wide Base

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	18220	19080	19920	20800	21600	22400	23200	24000	24800	25600	S	12800	LBS at	130 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	8280	8600	9060	9380	9700	10140	10460	10880	11180	11600	S	5800	KG at	900 kPa
	DUAL											D		KG at	kPa

455/55R22.5 LRL X One® XTE®*, X One® XDN®2

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	15000	15800	16580	17360	18120	18880	19640	20400	21200	22000	S	11000	LBS at	120 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	6800	7160	7520	7880	8220	8560	8900	9250	9580	10000	S	5000	KG at	830 kPa
	DUAL											D		KG at	kPa

455/55R22.5 LRM X One® XZY® 3, X One® XZU® S

PSI		85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		590	620	660	690	720	760	790	830	860	900				
LBS	SINGLE	16580	17360	18120	18880	19640	20400	21200	22000	22600	23400	S	11700	LBS at	130 PSI
	DUAL											D		LBS at	PSI
KG	SINGLE	7520	7880	8220	8560	8900	9250	9580	10000	10240	10600	S	5300	KG at	900 kPa
	DUAL											D		KG at	kPa

WHEEL DIAMETER - 24"

12.00R24 LRH XZY®

PSI		70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	12660	13320	13960	14560	15160	16100	16620	17140	17640		S	8820	LBS at	110 PSI
	DUAL	24480	25560	26600	27640	28640	29560	30440	31320	32200		D	8050	LBS at	110 PSI
KG	SINGLE	5740	6040	6340	6600	6880	7300	7540	7780	8000		S	4000	KG at	760 kPa
	DUAL	11120	11440	12080	12560	13000	13400	13800	14200	14600		D	3650	KG at	760 kPa

12.00R24 LRJ XDL®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	13320	13960	14560	15160	16100	16620	17140	17640	18200	18740	S	9370	LBS at	120 PSI
	DUAL	25560	26600	27640	28640	29560	30440	31320	32200			D	8540	LBS at	120 PSI
KG	SINGLE	6040	6340	6600	6880	7300	7540	7780	8000	8260	8500	S	4250	KG at	830 kPa
	DUAL	11440	12080	12560	13000	13400	13800	14200	14600	15040	15500	D	3875	KG at	830 kPa

WHEEL DIAMETER - 24.5"

11R24.5 LRG XZY® 3, XZE2™, XZA3® + EVERTREAD™, XZA® -1+, XTE®, XDN®2, XDE® M/S, XDA®5+, X® Line™ Energy D

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa		480	520	550	590	620	660	690	720						
LBS	SINGLE	9640	10140	10620	11100	11680	12190	12700	13220			S	6610	LBS at	105 PSI
	DUAL	18640	19480	20280	21040	22040	22700	23360	24020			D	6005	LBS at	105 PSI
KG	SINGLE	4380	4600	4820	5040	5300	5540	5780	6000			S	3000	KG at	720 kPa
	DUAL	8440	8840	9200	9560	10000	10320	10640	10900			D	2725	KG at	720 kPa

11R24.5 LRH XZY® 3, XZE2™, XDY-EX2™, XDS®2, XDN®2, XDE® M/S*, XDA®5+, X® MULTI™ ENERGY D, X® Line™ Energy T, X Works XDY®

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320	S	7160	LBS at	120 PSI
	DUAL	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440	D	6610	LBS at	120 PSI
KG	SINGLE	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500	S	3250	KG at	830 kPa
	DUAL	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000	D	3000	KG at	830 kPa

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your Michelin dealer for the applicable load and inflation table.

product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

Industry load and inflation standards are in a constant state of change, and Michelin continually

**S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle**

12R24.5 LRH

XZY[®] 3

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	11040	11580	12080	12790	13300	13820	14320	14760	15200	15660	S	7830	LBS at	120	PSI
	DUAL	21200	22080	22920	23360	24380	25400	26440	27160	27880	28640	D	7160	LBS at	120	PSI
KG	SINGLE	5000	5260	5480	5800	6040	6280	6500	6700	6900	7100	S	3550	KG at	830	kPa
	DUAL	9600	10000	10400	10600	11080	11560	12000	12320	12640	13000	D	3250	KG at	830	kPa

275/80R24.5 LRG

XZE2[™], XZA3[®]+ EVERTREAD[™], XZA[®]-1+, XTE[®], XDN[®]2, XDA[®]5+, X[®] Line[™] Energy T, X[®] Line[™] Energy D

PSI		70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	9090	9540	9880	10420	10840	11350	11670	12080	12350	S	6175	LBS at	110	PSI
	DUAL	16540	17360	18160	18960	19720	20820	21240	21980	22700	D	5675	LBS at	110	PSI
KG	SINGLE	4120	4320	4480	4720	4920	5150	5300	5480	5600	S	2800	KG at	760	kPa
	DUAL	7480	7880	8240	8600	8960	9440	9640	9960	10300	D	2575	KG at	760	kPa

305/75R24.5 LRJ

XZU[®]3

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	11360	11960	12550	13140	13720	14300	14860	15420	15980	16540	S	8270	LBS at	120	PSI
	DUAL	19660	20700	21740	22760	23760	24760	25740	26720	27680	28640	D	7160	LBS at	120	PSI
KG	SINGLE	5160	5400	5700	5940	6240	6460	6700	6980	7200	7500	S	3750	KG at	830	kPa
	DUAL	8960	9360	9880	10280	10840	11200	11600	12120	12480	13000	D	3250	KG at	830	kPa

